


HP Everyday Matte Polypropylene, 2 Pack



The HP Designjet printing system—the complete solution

HP Designjet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



- ¹ HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. See globalbmg.com/hp/ecosolutions for details.
- Using Original HP 70 Photo Inks or HP 83 UV inks. Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant-calculation assumes 6,000 Lux/12hr day. Prints require cold lamination to achieve prolonged display permanence on compatible HP Designjet printers using HP dye-based inks. For more information, see globalBMG.com/hplt/printpermanence.
- ³ Using Original HP 70 or 91 Photo Inks or HP 83 UV inks. Display permanence rating by HP Image Permanence Lab. Outdoor display permanence tested according to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Prints require cold lamination to achieve prolonged display permanence on compatible HP Designjet printers using HP dye-based inks. For more information, see globalBMG.com/hp/t/printpermanence.
- ⁴ Requires 2-inch spindle for compatibility with the HP Designjet L25500 and L26500 Printer series.

Print durable, high-impact signs

Produce high-impact signs with vibrant color

Produce retail and POP signage and event displays with vibrant color and eye-catching image quality. This matte polypropylene provides excellent versatility and value across a wide range of indoor and outdoor applications. And it's recyclable.¹

Print, use, handle, and laminate with ease

Maintain peak productivity. HP Everyday Matte Polypropylene is easy to use and handle, whether you're doing a quick print run or large production runs. Post-print processing is smooth and easy with this tear-resistant substrate.

Deliver durable output for indoor or outdoor use

To provide durable, long-lasting prints, Original HP printing materials are designed together with Original HP ink formulations. Prints achieve indoor, in-window display permanence up to 6 months;² outdoor display permanence up to 3 months.³

Target customers	Applications	Benefits Indoor and outdoor versatility	
Print service providers	POP/POS signs		
Retail store in-house printing	Retails displays	Tear resistance for easier handling	
Event designers	Event and trade show displays	Display permanence in-window up to 6 months, ² outdoor up to 3 months ³	
Advertising agencies	Posters	Broad HP Designjet printer compatibility ⁴	
Geographic Information Systems (GIS)		Recyclable through the HP Large Format Media take-back program ¹	
Government (printing maps)		Compatible with HP dye-and pigment-based inks	

Technical specifications



HP Everyday Matte Polypropylene, 2 Pack

For the latest ICC/media profiles and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit globalBMG.com/hp/.

Weight	120 g/m² per ISO	120 g/m² per ISO 536 Test Method							
Thickness	203 microns/8 m	203 microns/8 mil per ISO 534 Test Method							
Opacity	Greater than 96%	Greater than 96% per TAPPI T-425 Test Method							
Brightness	Greater than 1019	Greater than 101% per ISO 2470 Test Method							
Whiteness	Greater than 113	Greater than 113 per ISO 11476 Test Method							
Finish	Matte	Matte							
Operating temperature	15 to 30° C / 59 to	15 to 30° C / 59 to 86° F							
Operating humidity	20 to 80% RH	20 to 80% RH							
Display permanence (Commercial in-window)	Up to 6 months w	Up to 6 months with Original HP 70 Photo Inks or HP 83 UV inks ²							
Display permanence (Outdoor)	Up to 3 months w	Up to 3 months with Original HP 70 or 91 Photo Inks or HP 83 UV inks ³							
Water resistance	Water resistant ³	Water resistant ³							
Dry time	11 minutes (at 23	11 minutes (at 23° C, 50% RH)							
Lamination	Yes, cold								
Shelf life	1 year, unopened	1 year, unopened in original packaging							
Storage temperature	0 to 40° C / 32 to	0 to 40° C / 32 to 104° F							
Storage humidity	5 to 80% RH								
Recyclability	Recyclable throug	Recyclable through the HP Large Format Media take-back program ¹							
Country of origin	Product of China	Product of China							
	Product numbers	Quantity	Roll sizes	UPC Codes	Region				
Ordering information	CH022A ⁴	2 Pack	610 mm x 30,5 m (24 in x 100 ft)	848412013047	North America, Europe				
	CH023A ⁴	2 Pack	914 mm x 30,5 m (36 in x 100 ft)	848412013054	North America, Europe				
	CH025A ⁴	2 Pack	1067 mm x 30,5 m (42 in x 100 ft)	848412013061	Worldwide				
	CH026A ⁴	2 Pack	1270 mm x 30,5 m (50 in x 100 ft)	848412013078	North America, Europe				
	CH027A ⁴	2 Pack	1524 mm x 30,5 m (60 in x 100 ft)	848412013085	North America, Europe				
	CH024A ⁴	2 Pack	914 mm x 61 m (36 in x 200 ft)	848412013092	Americas, Europe				
Warranty	5	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see globalBMG.com/hp/MediaWarranties .							

HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. See globalbmg.com/hp/ecosolutions for details.

Using Original HP 70 Photo Inks or HP 83 UV inks. Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminantcalculation assumes 6,000 Lux/12hr day. Prints require cold lamination to achieve prolonged display permanence on compatible HP Designjet printers using HP dye-based inks. For more information, see globalBMG.com/hp/t/printpermanence.

Using Original HP 70 or 91 Photo Inks or HP 83 UV inks. Display permanence rating by HP Image Permanence Lab. Outdoor display permanence tested according to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Prints require cold lamination to achieve prolonged display permanence on compatible HP Designjet printers using HP dye-based inks. For more information, see globalBMG.com/hp/t/printpermanence.

Requires 2-inch spindle for compatibility with the HP Designjet L25500 and L26500 Printer series.



For detailed information on the HP large format printing materials portfolio and to order, see globalBMG.com/hp/

© 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

